

T5 Circline Plus

T5 Circline Plus 22W/830

0000520



Product features

-



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Circline
Colour temperature (K)	3000
CRI (Ra)	80
Dimmable	yes
EAN code	5410288005201
Energy class	A
Cap/Base	2GX13
Type	T5 Circline Plus
Watt (Nominal) (W)	22
Light colour	830 Warm White
Ordering number	0000520
Efficacy (Rated) (lm/w)	77
Average life (h) - L70/B50	16000
Luminous flux (Rated) (lm)	1800
Technology	Fluorescent

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
CRI (Ra)	80
Light colour	830 Warm White
Luminous flux (Nominal) (lm)	1800
Rated lumen maint. factor at 12000 h 50Hz	0.77

T5 Circline Plus

T5 Circline Plus 22W/830

0000520

Rated lumen maint. factor at 16000 h 50Hz	0.72
Rated lumen maint. factor at 2000 h 50Hz	0.85
Rated lumen maint. factor at 4000 h 50Hz	0.83
Rated lumen maint. factor at 6000 h 50Hz	0.82
Rated lumen maint. factor at 8000 h 50Hz	0.8
Luminous flux (Rated) (lm)	1800

General data

Average life (h) at Ta 25° C	16000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Circline
Dimmable	yes
EAN code	5410288005201
Energy class	A
Fixture rating	Close
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer;
IEC Reference	IEC 60081
IEC Reference 2	IEC 60901
Intended purpose	General lighting
Cap/Base	2GX13
Lamp mercury content (mg)	2.7
Type	T5 Circline Plus
Ordering number	0000520
Product name	T5 Circline Plus 22W/830
Average life (h) - L70/B50	16000
Rated survival factor at 12000 h 50Hz	0.78
Rated survival factor at 16000 h 50Hz	0.65
Rated survival factor at 20000 h 50Hz	0.5
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 4000 h 50Hz	0.97
Rated survival factor at 6000 h 50Hz	0.93
Rated survival factor at 8000 h 50Hz	0.85
Special purpose lamp	no

T5 Circline Plus

T5 Circline Plus 22W/830

0000520

Technology	Fluorescent
Transformer required	no
E-number FI	4940715

Electrical data

Current (A)	0.3
kWh per 1000 hours burning time	24
Watt (Nominal) (W)	22
Efficacy (Rated) (lm/w)	77
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	77
Watt (Rated) (W)	22
Watt (Rated) - High frequency (W)	22.3

Physical data

Max. Lamp Diameter (mm) - D	16
Lamp Length (mm) - C/L	225
Length base to base (mm) - A	225
Length base to pin Min-Max - B	225

T5 Circline Plus

T5 Circline Plus 22W/830

0000520

